

**MATERIAL SAFETY DATA SHEET**  
*(Oil-Only Sorbent Pads and Rolls)*

**SECTION I: IDENTIFICATION OF PRODUCT**

**PRODUCT NAME:** Oil-Only Sorbent Pads and Rolls (p/n's 82000 through 82006, 82150)  
**CHEMICAL FAMILY:** Olefin  
**PRODUCT USE:** Sorbent Media  
**CHEMICAL NAME:** Polypropylene

**COMPANY IDENTIFICATION**

Sellars Absorbent Materials, Inc.  
6565 N. 60th St.  
Milwaukee, WI 53223

**Emergency Telephone Number: 800-237-8454**  
**Telephone Number for Information: 800-237-8454 or 414-353-5650**

**WORK PLACE HAZARDOUS MATERIAL INFORMATION SYSTEM (WHMIS)**

**WHMIS CLASSIFICATION:** Not a Controlled Product Under WHMIS.  
**WORK PLACE HAZARD:** Not applicable.

**TRANSPORTATION OF DANGEROUS GOODS (TDG)**

**TDG CLASSIFICATION:** Not Dangerous Goods.  
**PACKAGE GROUP:** Not Applicable.  
**PRODUCT IDENTIFICATION NUMBER (PIN):** Not Applicable.

**SECTION II: HAZARDOUS INGREDIENTS**

<u>INGREDIENTS</u>	<u>PERCENT</u>	<u>CAS NUMBER</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Polypropylene	100%	9003-07-0		

Not A Hazardous Material Under WHMIS

**SECTION III: TOXICOLOGICAL PROPERTIES**

**HEALTH HAZARDS (acute or chronic):** None  
**SIGNS & SYMPTOMS OF EXPOSURE:** None  
**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** None

**SECTION IV: FIRST AID MEASURES**

No special procedures required.

**SECTION V: PHYSICAL DATA**

<b>APPEARANCE AND ODOR:</b>	White and virtually odor free
<b>SPECIFIC GRAVITY:</b>	0.88 – 0.92
<b>BOILING POINT ( C ):</b>	Not Applicable
<b>MELTING POINT ( C ):</b>	>160 C
<b>SOLUBILITY IN WATER:</b>	Insoluble
<b>PERCENT VOLATILE BY VOLUME:</b>	Not Applicable
<b>EVAPORATION RATE:</b>	Not Applicable
<b>VAPOR PRESSURE (mm Hg):</b>	Not Applicable
<b>VAPOR DENSITY (Air = 1):</b>	Not Applicable

**MATERIAL SAFETY DATA SHEET**  
**(Oil-Only Sorbent Pads and Rolls)**

**SECTION VI: FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** >329 C (625 F) (setchkin test)

**FLAMMABLE LIMITS:** Not Yet Determined

**EXTINGUISHING MEDIA:** Water, Foam, CO<sub>2</sub>, Dry Chemical

**SPECIAL FIRE FIGHTING PROCEDURES:** Standard procedures for Class A fires

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Some carbon monoxide formation is possible under oxygen-lean conditions. Matting will not support combustion.

**SECTION VII: REACTIVITY DATA**

**STABILITY:** Stable (XX)

**INCOMPATIBILITY (CONDITIONS TO AVOID):** None

**INCOMPATIBILITY (MATERIALS TO AVOID):** Avoid contact with hot or concentrated nitric and perchloric acid, sulfuric acid or 98% sulfuric acid at 60 C or above.

**HAZARDOUS POLYMERIZATION:** Will Not Occur (XX)

**SECTION VIII: PREVENTIVE MEASURES/SPECIAL PROTECTION INFORMATION**

**RESPIRATORY PROTECTION:** None Required

**VENTILATION:** None Required

**PROTECTIVE GLOVES:** None Required

**EYE PROTECTION:** None Required

**OTHER PROTECTIVE EQUIPMENT (SPECIFY):** None Required

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store in dry area. Do not store near open flame, high heat or strong oxidants.

Polypropylene, when heated, becomes very sticky and will burn.

Use self-contained air masks to enter smoky area in the event of fire.

**STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED**

No special steps to be taken if material is spilled or released.

**WASTE DISPOSAL METHOD**

Sanitary landfill or incineration site. Disposal must be done in accordance with local, state and federal regulations.

**SECTION IX: PREPARATION**

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

**DATE ISSUED:** Rev 1: 5/2/14