

Spill Kits Oil Only 55 Gallon Drum Spill Kit



- EverSoak® Oil Only 55 Gallon Drum Spill Kits are perfect for MRO (Maintenance, Repair & Operations) applications and should be stored indoors or underneath a protective cover if left outside
- ☐ Kit is made to handle medium sized spills.
- Kit has a lever lock allowing for quick access to spill control contents and saving valuable emergency spill response time
- Provides all of the necessary materials for helping clean up or contain oil, diesel fuel, grease, transmission fluid, coolants and many other types of liquid except water
- EverSoak® Oil Only 55 Gallon Drum Spill Kit contents are packed in a UN approved drum

- Contents: 75 Oil Only Sorbent Pads, 5 Oil Only Sorbent Socks, 4 Oil Only Sorbent Pillows, 2 Oil Only Sorbent Booms, 2 Pairs of Nitrile Gloves, 2 Pairs of Splash Resistant Goggles, 3 Disposal Bags and 2 GREENX™ HW ¼ Fold Bundles
- Oil Only 55 Gallon Drum Spill Kit contains EverSoak® sorbents which are made with 80% cotton and in independent lab tests shown to be more absorbent than the leading competitor's meltblown sorbents

Caution: EverSoak® Oil Only 55 Gallon Drum Spill Kit is not intended for use with aggressive acids or caustics. Dispose of all sorbent material according to local, state and federal regulations.

Spill Kits

Spills Happen. Be Prepared.

 Contains GREENX™ HW ¼ Fold Towels with 60 sheets per bundle



- First DRC Wiper to meet the EPA Comprehensive Procurement Guidelines.
- First DRC Wiper to be made with 40% post-consumer recycled fibers.*
- GREENX™ Towels provide opportunities to earn credits in several LEED-EB (Existing Buildings) Operation & Maintenance categories.
- * based only on the products's fiber content, which represents a minimum of 85% of the total product weight)



Made in the USA

OIL ONLY 55 Gallon Drum Spill Kit

Product Number:	99035
Drums Per Pallet:	8 drums/pallet
TI:	4 drums/layer
HI:	2 layers/pallet
Case Dimensions:	Length: 22.38"
	Width: 22.38"
	Height: 34.75"
Case Weight:	46 lbs
Pallets Per Truck:	30
UPC:	N/A

Absorbs up to 47 gallons of oil per kit

* per ASTM F726-06